

Eaton 9E3000IR

Catalog Number: 9E3000IR

Eaton 9E UPS, 3000 VA, 2700 W, Input: C20, Outputs: (6) C13, (1) C19, Rack, 2U

General Specifications



Product Name

Eaton 9E UPS

Catalog Number

9E3000IR

EAN

3553340710353

Product Length/Depth

608 mm

Product Height

86.5 mm

Product Width

438 mm

Product Weight

31.3 kg

Compliances

CE Marked
TUV

Certifications

IEC/EN 62040-1
IEC/EN 62040-2
CE

Battery

Battery type

Sealed, lead-acid

Runtime graph

\$row.attributeValue.cdata

Battery replacement

Replacable batteries

Battery quantity

6

Battery management

Temperature compensated
charging method
Automatic battery test
Deep discharge protection

Battery rating

12 V / 9 Ah

Extended battery capability

Yes

Electrical output

Receptacle

(6) C13 + (1) C19

Voltage

230V

Wattage

2700 W

Output power factor

0.9

Output voltage range

220/230/240 V +/- 2%

Output waveform

Sine wave

Output nominal voltage

230V default (220/230/240V)

Voltage distortion output (linear load) - max

3

Feed type

1

Topology

Online/Double-conversion

VA rating

3000 VA

Electrical input

Input connection

C14

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50/60 Hz

Input power factor

>.99

Input cord length

1.8m

Communications

Includes network card

No

Communication

USB port (HID compliant)
Serial port (RS232)
Mini-terminal block for
remote power off

Ethernet interface

No

User interface

Multilingual LCD display

Input frequency range
40-70 Hz

Potential free switch contact
Yes

Expansion slots
One slot for optional communication card

Software compatibility
Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

Type of interface
Other

Environmental

Additional specifications

Altitude
3000 m

Noise level
<45 dB at 1 meter

Temperature range
0° to 40°C (32° to 104°F)

Relative humidity
0-96% non-condensing

Construction type
482.6 mm (19 inch) device

Package contents
UPS
(2) IEC-IEC output cables
USB cable
Rack-mounting kit (rails and brackets)
Safety instructions
Quickstart guide

Phase (output)
1

Internal bypass
Yes

Auto shutdown function
Yes

Color
Black

Efficiency
91

Rack mounting kit
Yes

Phase (input)
1

Hot swap power
No

Resources

[Declarations of conformity](#)

[EU Declaration of Conformity](#)

[Manuals and user guides](#)

[9E Rack UPS quick start guide](#)

[Advanced user guide 9E Rack](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia