

Rittal – The System.

Faster – better – everywhere.

Small enclosures KX E-Box KX, sheet steel – KX 1550.000

Date : Jul 28, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Small enclosures KX E-Box KX, sheet steel – KX 1550.000

created: 28.07.2021 on www.rittal.com/com-en



Product description

Description:	The small enclosure KX, E-Box KX (sheet steel), offers remarkable ease of assembly and flexibility when selecting lock systems.
Material:	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal
Surface finish:	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 1, 3R, 4, 12
Type rating to UL 50E:	Type 1, 3R, 4, 12
IK Code:	IK08
Supply includes:	Enclosure with door Mounting plate Cam lock with 3 mm double-bit insert 180° hinge
Basic material:	Sheet steel

Product description

Dimensions:	Width: 200 mm Height: 400 mm Depth: 120 mm
Material thickness:	Enclosure: 1.25 mm Door: 1.25 mm Mounting plate: 2 mm
Mounting plate:	Width: 175 mm Height: 385 mm
Number of locks:	1
Packs of:	1 pc(s).
Weight/pack:	4.62 kg
EAN:	4028177816527
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	KXE-Box, WHD: 200x400x120 mm, sheet steel, with mounting plate, with door
Approvals	
Approvals:	Bureau Veritas DNV-GL Lloyds Register of Shipping UL + C-UL
Certificates:	Certificate of manufacturer according to RMRS Protection category
Declarations:	Declaration of conformity