

## Online UPS, 1000 VA

### EG-UPSO-1000

#### ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



#### Features

- Online type UPS: double voltage conversion without switching the power
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

#### Packaging

|                                |                |
|--------------------------------|----------------|
| Q'ty in crtn, pcs              | 1              |
| Crtn volume, CUM               | 0.0320256      |
| Crtn weight, kgs               | 10.6           |
| Individual package size LxWxH: | 400x240x320 mm |
| Carton size LxWxH:             | 417x240x320 mm |
| Country of origin              | CN             |
| Barcode                        | 8716309124836  |
| Customs code                   | 8504408590     |

#### Package contents

UPS  
Power cord  
USB cable  
Software CD  
Spare fuse

#### Specifications

UPS type: online, pure sine wave  
Input: 220V AC  $\pm 25\%$ , 50Hz / 60Hz  $\pm 10\%$   
Output: 220V AC  $\pm 1\%$ , 50Hz / 60Hz  $\pm 0.5\%$  (on battery)  
Output power factor:  $> 0.99$   
Inverter output efficiency (resistive load): 85%, any load type is allowed  
Switching time: zero  
Backup time: 8...20 mins (depends on the load)  
Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.35 kg x 2 pcs, 24VDC  
Charge time: 90% capacity restored in 3 hours  
External battery connectors: yes

#### System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

#### Certificates

