



LevelOne RJ45 to SFP Fast Ethernet Industrial Media Converter, -40°C to 75°C

Brand : LevelOne

Product code: IEC-4000

Product name : RJ45 to SFP Fast Ethernet Industrial Media Converter, -40°C to 75°C

10/100Mbps, RJ-45, 100Base-X SFP, 90 g

LevelOne RJ45 to SFP Fast Ethernet Industrial Media Converter, -40°C to 75°C:

LevelOne IEC-4000 is an industrial Fast Ethernet media converter with a mini size, rugged aluminium case which providing superb heat dissipation. This converter is designed to be mounted on an industrial standard DIN-rail, as well as on the wall, plus the clearly visible status LEDs provide simple monitoring of port link activity. It also features Link Fault Pass Through in order to alert remote location when link status changes.

10/100BaseT to 100Base-FX

- Rugged aluminium case design in a mini size form factor
- 18V-36VAC & 12V-60VDC with polarity protection
- Link Fault Pass through (LFP) function
- Supports switch and pure converter mode
- Surge & ESD protection
- Maximum noise & interference immunity
- 40°C to 75°C (-40°F to 167°F) operating temperature range
- DIN-Rail or panel mount installation



Network		Weight & dimensions	
Maximum data transfer rate *	100 Mbit/s	Height	36 mm
Converter input interface	10Base-T, 100Base-TX	Weight	90 g
Converter output interface	100Base-X	Operational conditions	
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x		
Flow control support	✓		
Auto MDI/MDI-X	✓		
Auto-negotiation	✓	Packaging content	
Store-and-forward	✓		
Duplex system	Full, Half	Quick installation guide	✓
Features		Packaging data	
Internal *	✗	Package width	160 mm
LED indicators	Activity, Link, Power	Package depth	105 mm
Product colour	Black	Package height	65 mm
Housing material	Aluminium	Package weight	260 g
Ports & interfaces		Package type	Box
		Certificates	
		Compliance certificates	RoHS
		Certification	
Connectivity technology	Wired		
Ethernet LAN (RJ-45) ports	1		
Fiber ports quantity	1		
Fiber optic connector *	SFP		
Power			
Input voltage	12 - 60 V		
Power consumption (typical)	1.44 W		
Weight & dimensions			
Width	59 mm		
Depth	49 mm		
		Logistics data	
		Harmonized System (HS) code	85176990



4015867188132

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.