



D-Link DGS-1100-24V2 Managed L2 Gigabit Ethernet (10/100/1000) 1U Black, Grey

Brand : D-Link

Product code: DGS-1100-24V2/E

Product name : DGS-1100-24V2



D-Link DGS-1100-24V2. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 8000 entries, Switching capacity: 48 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3x. Rack mounting, Form factor: 1U

Management features		Security	
Switch type *	Managed	Loop protection	✓
Switch layer	L2	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Web-based management	✓	Form factor	1U
Ports & interfaces		Product colour	Black, Grey
Basic switching RJ-45 Ethernet ports quantity *	24	LED indicators	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Performance	
Network		Flash memory	16 MB
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3x	Mean time between failures (MTBF)	424762 h
10G support *	✗	Power	
Port mirroring	✓	Power source *	AC
Full duplex	✓	Power supply included *	✓
Half duplex	✓	Number of power supply units	1
Flow control support	✓	AC input voltage	100 - 240 V
Link aggregation	✓	AC input frequency	50/60 Hz
Broadcast storm control	✓	Power consumption (max)	15.9 W
Rate limiting	✓	Power over Ethernet (PoE)	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	✗
Spanning tree protocol	✓	Operational conditions	
Head-of-line (HOL) blocking	✓	Operating temperature (T-T)	-5 - 50 °C
Ethernet LAN data rates	10,100,1000 Mbit/s	Storage temperature (T-T)	-40 - 70 °C
Auto-negotiation	✓	Operating relative humidity (H-H)	0 - 95%
VLAN support	✓	Storage relative humidity (H-H)	0 - 95%
Virtual LAN features	Port-based VLAN	Heat dissipation	54.3 BTU/h
Number of VLANs	128	Weight & dimensions	
Data transmission		Width	280 mm
Switching capacity *	48 Gbit/s	Depth	180 mm
Forwarding rate	35.71 Mpps	Height	44 mm
MAC address table *	8000 entries	Weight	1.32 kg
Jumbo frames support	✓	Sustainability	
Jumbo frames	9216	Sustainability compliance	✓
Packet buffer memory	4.1 MB	Certificates	
		Compliance certificates	BSMI, CB, CCC, cUL
		Certification	FCC, CE, VCCI, C-Tick, BSMI, CCC

Security

IGMP snooping 



0790069467844



790069467844



5704174940265

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.