

CyberPower PR3000ERT2UC uninterruptible power supply (UPS) Line-Interactive 3 kVA 3000 W 10 AC outlet(s)

Brand : CyberPower

Product code: PR3000ERT2UC

Product name : PR3000ERT2UC



- Line-interactive UPS Topology
 - Active PFC Compatible
 - Toolless Battery Replacement
 - High Output Power Factor
 - Overload Protection
 - Quick Charging Technology
 - Surge and Spike Protection
 - LCD Status Display
 - Serial Connectivity Port
 - PowerPanel Management Software
 - Built-in Remote Cloud Card by Ethernet
 - Energy Saving Technology
 - Pure Sine Wave Output
 - Battery Management Technology
 - Automatic Voltage Regulation (AVR)
 - Critical/Non-critical Load Outlets
 - Hot-swappable Batteries
 - EMI and RFI Filtration
 - USB Connectivity Port
 - Emergency Power Off (EPO) Port
 - SNMP/HTTP Remote Management Capability (Optional)
- Smart App UPS for Network and Server



Features		Battery	
UPS topology *	Line-Interactive	Number of batteries supported	1
Output power capacity *	3 kVA	Battery recharge time	3 h
Output power *	3000 W	Hot-swap battery	✓
Waveform *	Pure sine	Design	
Input operation voltage (min) *	200 V	Form factor *	Rackmount/Tower
Input operation voltage (max) *	240 V	Housing material	Metal
Input frequency *	50/60 Hz	Rack capacity	2U
Output operation voltage (min)	220 V	Extended battery module rack capacity	2U
Output operation voltage (max)	240 V	Cable length	3.05 m
Output frequency	50/60 Hz	Cooling type	Active
Automatic Voltage Regulation (AVR)	✓	Built-in fan	✓
Maximum current	16 A	Product colour *	Black
Surge energy rating	2430 J	Control type	Buttons
Response time	6 ms	Display type	LCD
Heat dissipation	96.7 BTU/h	LED indicators	✓
Number of input phases	1	Operational conditions	
Number of output phases	1	Operating temperature (T-T)	0 - 40 °C
Output power factor	1	Storage temperature (T-T)	-15 - 45 °C
Power Factor Correction (PFC) type	Active	Operating relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 95%
EMI/RFI noise filtering	✓	Operating altitude	0 - 3000 m
Surge protection	✓	Non-operating altitude	0 - 15000 m
Power protection features	Overload	Certificates	
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Compliance certificates	CE, Federal Communications Commission (FCC), RCM, RoHS, UL, VCCI
Power source type	AC		
Detachable power cord	✓		

Ports & interfaces		Packaging content	
AC outlet types	C13 coupler	Batteries included	✓
Power plug	C14 coupler	Rack mount kit	✓
AC outlets quantity	10 AC outlet(s)	Cables included	Serial
USB port	✓	Manual	✓
USB 2.0 ports quantity	1	Sustainability	
USB port type	USB Type-B	Sustainability compliance	✓
Serial interface	✓	Weight & dimensions	
Serial interface type	RS-232	Width	433 mm
Serial ports quantity	2	Depth	500 mm
RS-232 ports	2	Height	86.5 mm
Ethernet LAN (RJ-45) ports	2	Weight	32 kg
Emergency Power Off (EPO) connector	✓	Packaging data	
Battery		Package width	560 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	620 mm
		Package height	275 mm
		Package weight	38.8 kg
		Package type	Box
		Logistics data	
		Country of origin	China
		Other features	
		Battery type	RBP0128



4711027798905

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.