



Lindy 150m Cat.6 HDMI 4K60 & Type C HDBaseT UK Wall Plate KVM Extender, Transmitter

Brand : Lindy

Product code: 38387

Product name : 150m Cat.6 HDMI 4K60 & Type C HDBaseT UK Wall Plate KVM Extender, Transmitter

- Sends HDMI or Type C signals up to 150m over Cat.6 network cable via HDBaseT technology with Long Reach mode
- Supports HDMI 18G resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- Supports USB 2.0, Audio, RS-232, bi-directional IR and PoC (Power over Cable)
- UK standard 1-gang wall plate (86x86mm)

150m Cat.6 HDMI 4K60 & Type C HDBaseT UK Wall Plate KVM Extender, Transmitter

Lindy 150m Cat.6 HDMI 4K60 & Type C HDBaseT UK Wall Plate KVM Extender, Transmitter. Type:

Transmitter, Connectivity technology: Wired, Maximum transfer distance: 150 m. Transmitter video port type: HDMI. Receiver local video port type: HDMI. USB port type: USB Type-C. AC input voltage: 24 V, Input current: 1 A



Features		Packaging data	
Type *	Transmitter	Package width	152 mm
Connectivity technology *	Wired	Package depth	95 mm
Maximum transfer distance	150 m	Package height	133 mm
Cable types supported	Cat6	Package weight	540 g
Maximum digital resolution	3840 x 2160 pixels	Packaging content	
Maximum refresh rate	60 Hz	Manual	✓
Colour depth	8 bit	Operational conditions	
Material	Metal, Plastic	Operating temperature (T-T)	0 - 40 °C
LED indicators	✓	Storage temperature (T-T)	-20 - 60 °C
Certification	CE, UKCA, FCC, RoHS, REACH, California Proposition 65	Operating relative humidity (H-H)	20 - 90%
Transmitter		Storage relative humidity (H-H)	20 - 90%
Transmitter video port type	HDMI	Sustainability	
RJ-45 ports quantity (transmitter)	1	Sustainability compliance	✓
Receiver		Other features	
Receiver local video port type	HDMI	HDCP	✓
RJ-45 ports quantity (receiver)	1	HDCP version	2.2
Ports & interfaces		Extended display identification data (EDID)	✓
USB port type	USB Type-C	Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
HDMI version	2.0	Technical details	
RS-232 ports	1	Dimensions (WxDxH)	86 x 38.05 x 86 mm
Power		Maximum resolution	3840 x 2160 pixels
AC input voltage	24 V	Weight	390 g
Input current	1 A		

Logistics data

Quantity per pack

1 pc(s)



4002888383875

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.