



Dahua Technology Lite HAC-HFW1500R-Z-IRE6-S2 Bullet CCTV security camera Outdoor 2880 x 1620 pixels Ceiling/Wall/Pole

Brand : Dahua Technology

Product family: Lite

Product code: DH-HAC-HFW1500RP-Z-IRE6-2712-S2

Product name : HAC-HFW1500R-Z-IRE6-S2

Dahua Technology Lite HAC-HFW1500R-Z-IRE6-S2. Type: CCTV security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Bullet. Angle of rotation: 360°, Lens viewing angle, horizontal: 34 - 107°, Lens viewing angle, vertical: 19 - 55°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Focal length range: 2.7 - 12 mm, Detect distance (wide): 69 m, Detect distance (tele): 191.6 m

Performance		Night vision	
Type *	CCTV security camera	Night vision distance	60 m
Placement supported *	Outdoor	LED type	IR
Connectivity technology *	Wired	Number of illumination LEDs	4
Day/night mode	✓	Video	
Luminous flux	0.005 lm	Maximum resolution *	2880 x 1620 pixels
Design		Total megapixels *	5 MP
Form factor *	Bullet	Supported graphics resolutions	
Mounting type *	Ceiling/Wall/Pole	960 x 480, 960 x 576, 1920 x 1080 (HD 1080), 2560 x 1440, 2880 x 1620	
Product colour *	White	Frame rate	25 fps
Housing material	Metal	Noise reduction	✓
International Protection (IP) code	IP67	Noise reduction technology	2D noise reduction
Display diagonal	2.54 cm (1")	Gain control type	Auto/Manual
Camera		Flip & mirror	✓
Angle of rotation	360°	Privacy masking	✓
Lens viewing angle, horizontal	34 - 107°	Back Light Compensation (BLC)	✓
Lens viewing angle, vertical	19 - 55°	Highlight Compensation (HLC)	✓
Lens viewing angle, diagonal	39 - 130°	Digital Wide Dynamic Range (DWDR)	✓
Tilt angle range	0 - 78°	Smart IR	✓
Pan range	0 - 360°	Ports & interfaces	
White balance	Auto, Manual	BNC output ports	1
Camera shutter speed	1/25 - 1/1000000 s	Power	
Number of Privacy masking areas	8	Power source type *	DC
Image sensor		Power consumption (typical)	9.8 W
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	DC output voltage	12
Progressive scan	✓	Operational conditions	
Sensor type *	CMOS	Operating temperature (T-T)	-30 - 60 °C
Lens system		Storage temperature (T-T)	-30 - 60 °C
Number of lenses *	1	Operating relative humidity (H-H)	0 - 95%
Focal length range	2.7 - 12 mm	Storage relative humidity (H-H)	0 - 95%
Minimum aperture number	1.6	Weight & dimensions	
Detect distance (wide)	69 m	Width	209.9 mm
Detect distance (tele)	191.6 m	Depth	90.4 mm
Observe distance (wide)	27.6 m	Height	90.4 mm
Observe distance (tele)	76.64 m	Weight	550 g
Recognize distance (wide)	13.8 m	Packaging data	
Recognize distance (tele)	38.32 m	Package weight	700 g
Identify distance (wide)	6.9 m		
Identify distance (tele)	19.16 m		
Closest focusing distance	0.5 m		

Night vision		Sustainability	
Night vision *	✓	Compliance certificates	CE, Federal Communications Commission (FCC), UL
		Packaging content	
		Number of cameras *	1

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.