



Dahua Technology DH-CS4010-8ET-60 network switch Managed L2 Fast Ethernet (10/100) Power over Ethernet (PoE) Black



Brand : Dahua Technology

Product code: DH-CS4010-8ET-60

Product name : DH-CS4010-8ET-60

10-Port Cloud Managed Desktop Switch with 8-Port PoE

Dahua Technology DH-CS4010-8ET-60 network switch Managed L2 Fast Ethernet (10/100) Power over Ethernet (PoE) Black:

Highly intuitive, the Smart Managed Switch can manage local networks. With the DoLink Care platform, it can also perform cloud management. The switch performs operation and maintenance using topology visualization on front-end, transmission and back-end storage devices that are in the security system and IT system. With its full metal design, the switch has great heat dissipation and can operate in temperatures ranging -10°C to 55°C. It offers EMC and has protection against overvoltage, overcurrent, static electricity, lightning strikes, pulses and other types of interference. For the PoE series Smart Managed Switch, power is supplied up to 250 meters away. The orange port supplies up to 60 W and the red port provides up to 90 W. The switch can be used in small and medium-sized businesses such as supermarkets, offices, restaurants, cafés and hotels.

Management features		Design	
Switch type *	Managed	Product colour	Black
Switch layer	L2	Housing material	Metal
Quality of Service (QoS) support	✓	Reset button	✓
Web-based management	✓	LED indicators	✓
Cloud-managed	✓	Power	
Ports & interfaces		Power source *	DC/PoE
Basic switching RJ-45 Ethernet ports quantity *	8	Power supply included *	✓
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	Redundant power supply (RPS) support	✓
Fast Ethernet (copper) ports quantity	8	DC input voltage	53 V
Gigabit Ethernet (copper) ports quantity	2	Input current	1.226 A
Network		Power consumption (max)	65 W
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✓
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE) ports quantity	8
Flow control support	✓	Operational conditions	
Ethernet LAN data rates	10,100,1000 Mbit/s	Operating temperature (T-T)	-10 - 55 °C
VLAN support	✓	Storage temperature (T-T)	-40 - 70 °C
Virtual LAN features	Port-based VLAN	Operating relative humidity (H-H)	5 - 95%
Number of VLANs	32	Storage relative humidity (H-H)	5 - 95%
Data transmission		Weight & dimensions	
Switching capacity *	4.8 Gbit/s	Width	130 mm
Forwarding rate	3.57 Mpps	Depth	90 mm
MAC address table *	8000 entries	Height	26 mm
Jumbo frames support	✓	Weight	280 g
Jumbo frames	9216	Packaging data	
Packet buffer memory	4 MB	Package width	265 mm
Security		Package depth	238 mm
DHCP features	DHCP client	Package height	76 mm
		Package weight	800 g
		Sustainability	
		Sustainability compliance	✓

Design		Certificates	
Rack mounting *	✗	Compliance certificates	CE

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.