



Dahua Technology Lite HAC-HDW1500T-Z-A-POC Turret CCTV security camera Indoor & outdoor 2880 x 1620 pixels Ceiling/Wall/Pole

Brand : Dahua Technology

Product family: Lite

Product code: HAC-HDW1500T-Z-A-2712-S2

Product name : HAC-HDW1500T-Z-A-POC



- The parameters and datasheets below can only be applied to 1500-S2 series
- Max 25 fps@5MP (16:9 video output)
- CVI/CVBS/AHD/TVI switchable
- 2.7 mm-12 mm motorized lens
- Built-in mic
- Max. IR length 60 m, Smart IR
- IP67, PoC (only CVI)/12V±30% DC
- 1/2.7, CMOS, 2880x1620, 5MP, 1/25 s-1/100000 s, 1/30 s-1/100000 s, 65 dB, 60 m, 0°-360°, 0°-78°, 0°-360°

Dahua Technology Lite HAC-HDW1500T-Z-A-POC. Type: CCTV security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: Black, White, Form factor: Turret. Minimum illumination: 0.005 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 107°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Focal length range: 2.7 mm, Closest focusing distance: 0.5 m

Performance		Night vision	
Type *	CCTV security camera	LED type	IR
Placement supported *	Indoor & outdoor	Number of illumination LEDs	2
Connectivity technology *	Wired	Video	
Wide Dynamic Range (WDR)	✓	Maximum resolution *	2880 x 1620 pixels
Day/night mode	✓	Total megapixels *	5 MP
Certification	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014, EN 62368-1:2014+A11:2017) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)	Noise reduction	✓
		Noise reduction technology	2D noise reduction
		Gain control type	Auto/Manual
		Privacy masking	✓
		Back Light Compensation (BLC)	✓
		Digital Wide Dynamic Range (DWDR)	✓
		Smart IR	✓
Design		Audio	
Form factor *	Turret	Signal-to-Noise Ratio (SNR)	65 dB
Mounting type *	Ceiling/Wall/Pole	Storage	
Product colour *	Black, White	Built-in HDD *	✗
Housing material	Metal	Security	
International Protection (IP) code	IP67	Mirror	✓
Camera		Power	
Minimum illumination	0.005 lx	Power source type *	DC, PoC
Angle of rotation	360°	Power consumption (max)	6.6 W
Lens viewing angle, horizontal	107°	DC output voltage	12
Lens viewing angle, vertical	55°	Operational conditions	
Lens viewing angle, diagonal	130°	Operating temperature (T-T)	-30 - 60 °C
Tilt angle range	0 - 78°	Storage temperature (T-T)	-30 - 60 °C
Pan range	0 - 360°	Operating relative humidity (H-H)	0 - 95%
White balance	Auto, Manual	Storage relative humidity (H-H)	0 - 95%
Image sensor		Weight & dimensions	
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Depth	104.8 mm
Sensor type *	CMOS		

Lens system		Weight & dimensions	
Number of lenses *	1	Height	122 mm
Focal length range	2.7 mm	Weight	570 g
Maximum aperture number	1.6	Packaging data	
Closest focusing distance	0.5 m	Package weight	702 g
Night vision		Packaging content	
Night vision *	✓	Number of cameras *	1
Night vision distance	60 m		



6939554949784

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.