



APC Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

Brand : APC

Product code: SRT1000RMXLI



Product name : Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

[APC Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit:](#)

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1000VA on-line 2U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with IEC 320 C14, BS1363A British and Schuko CEE 7/EU1-16P inputs, and 6x IEC 320 C13 outlets. It has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty.



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount/Tower
Output power capacity *	1 kVA	Cable length	1.5 m
Output power *	1000 W	Product colour *	Black
Waveform *	Sine	LED indicators	Status
Input operation voltage (min) *	50 V	International Protection (IP) code	IP20
Input operation voltage (max) *	150 V	Operational conditions	
Input frequency *	40/70 Hz	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (min)	220 V	Storage temperature (T-T)	-20 - 50 °C
Output operation voltage (max)	240 V	Operating relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Storage relative humidity (H-H)	0 - 95%
Surge energy rating	432 J	Certificates	
Crest factor	3:1	Compliance certificates	RoHS
Emergency Power Off (EPO)	✓	Certification	CE, EAC
Noise level	50 dB	Packaging content	
Audible alarm(s)	✓	Management card included	✗
Ports & interfaces		Sustainability	
AC outlet types	C13 coupler	Sustainability certificates	Green Premium
AC outlets quantity	6 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	432 mm
USB 2.0 ports quantity	1	Depth	505 mm
Serial interface	✓	Height	85 mm
Serial interface type	RJ-45	Weight	21 kg
SmartSlot	✓	Packaging data	
SmartConnect port	✗	Package width	594 mm
Battery		Package depth	749 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	246 mm
Battery life (max)	5 year(s)		

Battery		Packaging data	
Battery recharge time	3 h	Package weight	29.6 kg
Hot-swap battery	✓	Logistics data	
		Products per pallet	12 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	1843.14



0731304340256



731304340256

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.