

NETGEAR XS505M Unmanaged 10G Ethernet (100/1000/10000) Grey, Silver

Brand : NETGEAR

Product code: XS505M-100EUS

Product name : XS505M



NETGEAR XS505M. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 4. Full duplex. MAC address table: 2000 entries, Switching capacity: 100 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3aq, IEEE 802.3az,.... Power connector: DC-in jack. Rack mounting

Management features		Power	
Switch type *	Unmanaged	Power source *	AC
Quality of Service (QoS) support	✓	AC input voltage	100 - 240 V
Ports & interfaces		AC input frequency	50 - 60 Hz
Basic switching RJ-45 Ethernet ports quantity *	4	Input current	1.5 A
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Power consumption (typical)	12.25 W
SFP+ module slots quantity	1	Power consumption (max)	22.5 W
Power connector	DC-in jack	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✗
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3aq, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Operational conditions	
10G support *	✓	Operating temperature (T-T)	0 - 50 °C
Full duplex	✓	Storage temperature (T-T)	-20 - 70 °C
Flow control support	✓	Operating relative humidity (H-H)	0 - 95%
Data transmission		Storage relative humidity (H-H)	0 - 95%
Switching capacity *	100 Gbit/s	Operating altitude	0 - 3000 m
MAC address table *	2000 entries	Heat dissipation	85.3 BTU/h
Jumbo frames support	✓	Weight & dimensions	
Jumbo frames	9000	Width	328 mm
Packet buffer memory	128 MB	Depth	169 mm
Design		Height	43.2 mm
Rack mounting *	✓	Weight	1.38 kg
Product colour	Grey, Silver	Certificates	
LED indicators	✓	Certification	47 CFR FCC, ICES-003:2016 Issue 6, ANSI C63.4:2014, EN 55032:2012+AC2013, EN 55024:2010, EN 61000-3-2:2014, EN 6100-3-3:2013, AS/NZS CISPR 32:2015, VCCI V-3/2015.04, V-4/2012.4, CNS 13438
Safety	CE: CB 60950-1, LVD 60950-1, AUS/NZ: AS/NZS 60950-1, USA: UL 60950-1, SNE VA, BSMI	Logistics data	
Performance		Harmonized System (HS) code	85176990
Mean time between failures (MTBF)	1093237 h		



0606449131130



606449131130

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.